



Unique Exchange Heater Module



Patent Pending
 Community Design No: 000235429
 UK Registered Design No: 2098802

Features / Benefits

- Working Pressure - 238 bar / 3500 psi
- Flow Rate - 12ltr/min 2.6 gpm
- Max Operating Temp - 75°C
- Pressure & Flow fully variable on throttle
- Choice of Diesel or Petrol Models
 - Honda iGX Option for quieter operation
- Water Tank Capacity 800ltr approx
- Automatic Anti-freeze Pump System
- High Temp PTFE Pump Seals
- Revolutionary Quick Release Heater Module
 - Fully part exchange service package available

HWBBW

- Max Pressure:** 3500 PSI / 238 BAR
- Volume:** 2.6 GPM / 12.0 LPM
- Pump:** Triple piston Cat Pump
- Engine:** Choice of Diesel or Petrol Models
- Drive:** Triple Vee Belt Drive
- Delivery Hose:** 15m 3/8" braided with Quick Screw adaptor
- Gun:** With swivel coupling and Quick Screw adaptor
- Lance:** 1m two piece stainless steel lance
- Dimensions:** 1085mm x 600mm x 670mm
- Chemical System:** Metered high pressure chemical system with chemical inlet hose and filter

Unique Brendon Live Hose Reel and lance carrier, complete with Brendon Powerwasher mounted on a robust tubular chassis with rear protection bar, single axle trailer with full track rubber suspension and heavy duty jockey wheel. Overrun and hand parking auto reversing brakes and lighting, to full highway regulation. Anti-freeze and chemical tanks can be adapted for other uses if required

Specification may differ per country. Brendon reserves the right to alter the specification without notice.



Anti-Freeze Pump



Hinged Rear Panel



Easy Maintenance



Covered Control Panel